

CP-510 PORTABLE TWO-WAY RADIO

**BUILT TOUGH TO
DO BUSINESS BETTER.**

FEATURE HIGHLIGHTS

- IP55 rating splash and dust proof
- Ultra crisp and clear audio
- Multi-icons backlit LCD display
- 2200mAh Li-ion battery and life up to 60 hours
- 200 programmable channels
- 50 CTCSS tones & 210 DCS codes in TX and RX
- High/low output power selectable
- Built-in VOX for hands-free communications
- FM radio receiver (76 - 108MHz)
- Emergency alarm
- VFO/Memory channel mode
- PC programmable



**RUGGED, HEAVY-DUTY AND DURABLE
OUTLAST HARSH CONDITIONS AND HARD USE
EXCEPTIONALLY CLEAR AUDIO**

SPECIFICATIONS

General

Frequency	VHF: 136-174MHz	UHF: 400-480MHz
Channel capacity	200 channels	
Power supply	7.4V DC	
Dimensions (without belt clip and antenna)	112mm (H) x 57mm (W) x 35mm (D)	
Weight (with battery and antenna)	270g	

Transmitter

RF Power	1W / 5W	1W / 4W
Channel spacing	12.5 / 25kHz	
Frequency Stability (-30°C to +60°C)	±1.5ppm	
Modulation Deviation	≤ 2.5kHz / ≤ 5kHz	
Spurious & Harmonics	-36dBm < 1GHz, -30dBm > 1GHz	
FM Hum & Noise	-40dB / -45dB	
Adjacent Channel Power	≥ 60dB / 70dB	
Audio Frequency Response (Preemphasis, 300 to 3000Hz)	+1 ~ -3dB	
Audio Distortion @1000Hz, 60% Rated Max. Dev.	< 5%	

Receiver

Sensitivity (12 dB SINAD)	≤ 0.25μV / ≤ 0.35μV	
Adjacent Channel Selectivity	- 60dB / -70dB	
Audio Distortion	< 5%	
Radiated Spurious Emissions	-54dBm	
Intermodulation Rejection	-70dB	
Audio Output @ < 5% Distortion	1W	

STANDARD ACCESSORIES



LB-220



AC Adapter



Desktop Charger



ANT-500



BC-S1

MADE IN CHINA

Welcome the cooperation for OEM and ODM !

With the advantage of strong R&D, design force and rich experience in OEM/ODM service, we can better meet the specific demand of partners and help them increase their brand value and competitive advantage.

For more information about our products, please contact us:

🌐 www.samradios.com 📞 +86-595-86713710 ✉ info@samradios.com

SAMCOM
TWO-WAY RADIO

